



IMPORTANT TURN OFF THE POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE STARTING INSTALLATION

NOTE: Carefully unpack and identify all parts before assembly. Bulbs are not included.

1. Spread open arms till they are evenly spaced to each other. **NOTE:** Please see fig. 2 for upper tier arms position against lower tier arms from top view.
2. Thread fixture wire and ground wire thru center hole of loop. Then fasten loop securely onto top fixture threaded pipe.
3. Remove counter rings from side sockets. Attach side glass shades onto side sockets by fastening with counter ring.
4. Screw bottom threaded pipe into coupler.
5. Sit pan on top of center glass shade and slip them thru bottom threaded pipe. Secure them with washer and hex nut until pan gently touches bottom rods. **NOTE:** Glass checks into Lip on outside of pan. L-bracket of bottom rods must be located inside of pan. (See Fig 3.)
6. Slip fitter thru remaining bottom threaded pipe and secure with finial. Do not over tighten.
7. Install light bulbs (not included). See relamping label which is located at socket areas, for type and maximum allowed wattage.
8. Follow enclosed "**Over 50lbs. Chain Suspended Fixture Assembly**" for electrical installation and fixture installation to outlet box.

