



Product Specifications for EC95018-PC

Job Name:	Job Type:
Quantity:	Comments:



EC95018-PC
RapidJack 7-Light Canopy

Finish
Polished Chrome

Glass/Shade

Product Category
Pendant Accessory

Lamping

Number of Bulb(s)	N/A
Light Type	N/A
Bulb Type	
Max Bulb Wattage	N/A
Max Fixture Wattage	
Rated Life	N/A
Rated Lumens	±0
Color Temp	N/A
Bulb(s) Included	No
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	Yes
Dimmable	Low-Voltage

Measurements

Width	17.00"
Height	2.50"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	N/A
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	17.0"
Canopy Height	2.5"
Canopy Length	N/A

Shipping

Carton Weight	N/A
Carton Width	N/A
Carton Height	N/A
Carton Length	N/A
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

UL Standard	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Other

UPC Code	845094058380
Material	N/A

Equivalents

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2012 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material. ET2 Contemporary Lighting products are UL, ETL or CSA approved. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.