



GLIDE

12V MINI PENDANTS

location:
DRY

SPECIFICATIONS:

DESCRIPTION

Low voltage mini pendant with concrete lamp cover.

LAMPING

Standard: 20W Shielded flood 12V halogen MR11 lamp, lamp included.

LED: 3W Replaceable 12V LED MR11, dimmable, 82+ CRI, 2700°K CCT, 230 lumens, 40,000 hours. Lamp included.

DIFFUSER

Shade shall be made of concrete in various finishes. 2" Dia. x 4" H

CORD

Standard cord is 10' field-adjustable coaxial type with teflon jacket and decorative sleeve at the socketholder. Jacket tint coordinates with metal finish.

STANDARD PENDANT

Mini pendant comes complete with flat-style canopy.

METAL FINISH


Hardware and canopies are finished in Bronze or Satin Nickel.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



NATURAL (GLIDENA), WHITE (GLIDEWH) & TAN (GLIDETN) WITH BRONZE FINISH



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 3/16



GLIDE

12V MINI PENDANTS


ORDERING:

CONNECTION	SHADE OPTIONS	LAMP OPTIONS	METAL FINISH
Pendant Fixtures	GLIDENA Natural	(blank) 20W MR11 Hal	BR Bronze
1XT Flat Canopy	GLIDETN Tan	LED 3W LED	SN Satin Nickel
	GLIDEWH White		

Ex. 1XT-GLIDEWH-SN
 Glide Pendant, White,
 Satin Nickel Finish

FIXED PENDANT OPTION:

1XT 1 Light Pendant, Flat Canopy



- Suitable for use on sloped ceilings
- 1x electronic 60W dimmable 120V transformer, fits partially in junction box
- Installs to standard 4" octagonal junction box
- Bronze or Satin Nickel metal finishes

12V LED MR11 TYPE LAMPS:

3W Replacable LED:

- 3W LED lamp
- 230 lumens
- 12V input only
- Rated life: 40,000 hours
- CRI: 82+
- CCT: 2700°K
- Dimmable

Project Information: