



KAILEE

SCONCES WALL

ADA COMPLIANT CHOICE COLLECTION location: DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-top handcrafted glass.

LAMPING

Standard: 60W E12 120V incandescent, suitable for dimming. not included.

CFL: 13W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V, lamp not included.

LED: 6W LED Replaceable source, 120V, non-dimmable, included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 6.5" W x 4" H) shall be constructed of steel, powder-coated white.

METAL FINISH

Decorative metal accents shall be in various finish options.

MOUNTING


Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.75" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



KAILEE SHOWN IN HONEY (7017HN) & GARNET (701741)



For ordering information, see next page

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



KAILEE

SCONCES WALL

ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
701707 Opal Matte	(blank) 60W E12 Incan	BK Black	LW Low Wattage
701718 Amber Cloud	D1 13W Quad 120V	BR Bronze	labeling
701719 Carrera	M1 13W Quad 277V	PN Polished Nickel	
701741 Garnet	GU24 13W GU24 120V	SN Satin Nickel	
701780 Amber Matte	LED 6W LED 120V,	WH White	
701786 Blue Cloud	non-dimmable		
7017CE Ceylon			
7017HN Honey			
7017HV Halva			
7017VM Vanilla Matte			

Ex. 701741-SN
 Kailee Wall Sconce w/ Garnet Glass,
 Satin Nickel Finish

LED 120V PENDANTS:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 6 watts
- Non-dimmable
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 300 lumens
- CCT: 2700° Kelvin
- CRI: 80+

Project Information: