



LINA

SCONCES WALL



location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted **ADA-compliant** sconce featuring open-top handcrafted glass.

LAMPING

Standard: 75W A19 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 18W max, 120V, lamp not included.

LED: 10W LED Replaceable source, 120V, dimmable, included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4"W x 6.5" H) shall be constructed of steel, powder-coated white.

METAL FINISH


Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 3.625" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



LINA SHOWN IN VANILLA MATTE (7083VM), AMBER MATTE (708380) & OPAL MATTE (708307)

ORDERING:

FIXTURE/DECOR	LAMP OPTIONS	METAL FINISH	OPTIONS
708307 Opal Matte	(blank) 75W A19 Incan	BK Black	LW Low Wattage
708380 Amber Matte	E1 18W Quad 120V	BR Bronze	labeling
7083VM Vanilla Matte	N1 18W Quad 277V	PN Polished Nickel	
	GU24 18W GU24 120V	SN Satin Nickel	
	LED 10W LED 120V, dimmable	WH White	

Ex. 708307-SN

Lina Wall Sconce w/ Opal Matte Glass, Satin Nickel Finish

Project Information:

LED SCONCES:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14