

MONORAIL

MONORAIL SPIRAL

DESCRIPTION

Monorail is rated for 300 watts at 12 volts and 600 watts at 24 volts. Each piece of rail is shipped with straight conductive connectors to join rail pieces end to end. Order additional connectors (p. 461) if cutting and rejoining rails. All pieces are field-cuttable and hand-bendable to a horizontal radius as small as 6 inches.




BRONZE



SATIN NICKEL

32" MONORAIL SPIRAL

Kit includes: Custom bent Monorail, Straight Conductive Connectors and End caps. (5) Standoffs required (sold separately). 32" Spiral.




MODEL	RAILCVSPRL-
FINISH	BZ32 bronze SC32 satin nickel

sample item number **RAILCVSPRL-BZ32** 32" monorail spiral, bronze

48" MONORAIL SPIRAL

Kit includes: Custom bent Monorail, Straight Conductive Connectors and End caps. (7) Standoffs required (sold separately). 48" Spiral.



MODEL	RAILCVSPRL-
FINISH	BZ48 bronze SC48 satin nickel

sample item number **RAILCVSPRL-SC48** 48" monorail spiral, satin nickel

FIXTURE TYPE _____

JOB NAME _____

NOTES _____



7400 Linder Ave.
Skokie, Illinois 60077

T 847.626.6300
F 847.626.6350

lblighting.com



© 2014 LBL Lighting. All rights reserved. The "LBL Lighting" graphic is a registered trademark of LBL Lighting. LBL Lighting reserves the right to change specifications for product improvements without notification.